



09/763,092
"SUBSTITUTE SPECIFICATION
& ABSTRACT"

SPECIFICATION

SWING ARM FOR TWO-WHEELED MOTOR VEHICLE AND METHOD OF PRODUCING
THE SAME

TECHNICAL FIELD

The present invention relates to a swing arm for a two-wheeled motor vehicle, and more particularly relates to a swing arm for preventing an abnormal sound which may be produced due to resonance with vibrations of an engine, and relates to a method of producing the swing arm.

TECHNICAL BACKGROUND

A two-wheeled motor vehicle, such as a motorcycle, has a suspension device provided therewith for not transmitting ^{preventing transfer of} vertical movements of tires due to irregular road surfaces to the body of the motor vehicle and to a rider thereon, and for sufficiently transmitting the driving force of an engine to a road surface through the rear wheel. A suspension device is generally provided at both the front and rear ^{ends} sides of the vehicle body. ✓

The suspension device provided at the rear ^{end} side is, as shown in Fig. 22, composed of a spring 101 for receiving a load, a shock absorber 102 for absorbing vibrations produced by the reaction force of the spring, and a swing arm 103 positioning

the movements of the wheel.

The swing arm 103 is composed of a pair of arm portions pivotally mounted to the frame of the vehicle and a body portion connecting the pair of arms. The arm portion is generally made of an elongated member of an aluminum drawn tube which is widened in the vertical direction with respect to the vehicle for providing stiffness thereto. The body portion is cast aluminum with a hollow part molded in the form of a box through a vertical pair of casting dies. ✓

The swing arm is formed so as to have sufficient stiffness and is made of a metal, for example, aluminum. A technique is known by which the swing arm is ^{made} provided with ⁱⁿ a hollow part ^{includes} therein to reduce the weight. However when the swing arm ^{is} provided with ^{the} hollow portion, ^{it} has been inconvenient ^{because} the wall surrounding the hollow portion resonates with the vibrations from the engine and produces noise during running because the swing arm is disposed in the vicinity of the engine of the two-wheeled motor vehicle.

To eliminate ^{the problem of resonance} such inconvenience, swing arms of such structures have been provided with a rib extending from an upper part of the body to a lower part ^{of the body} thereof for connecting the upper and lower parts to increase the strength and control vibrations. ^{Alternatively,} otherwise, an inner wall is provided within the hollow portion of the arm or the body portions so as to control

the vibrations in the arm or body portions and prevent the swing arm from resonating with the vibrations from the engine.

However for fabricating swing arms having such structures, it is required to provide a rib or an inner wall. This makes the shape of the casting die complicated and increases the casting steps. Further, it is required to form a rib or inner wall at the arm portion or the body portion in ^a balanced ^{manner} condition, which makes the production troublesome and ^{is} more costly. ✓ ✓ ✓

DISCLOSURE OF THE INVENTION

~~The present invention has been made to eliminate the problems and disadvantages mentioned above. It is accordingly an object of the invention to provide a swing arm for a two-wheeled motor vehicle which is simple in structure and is effective for preventing resonance with vibrations from the engine.~~

~~The invention will be explained in accordance with claimed embodiments.~~

The swing arm of the invention is disposed at the rear part of the two-wheeled motor vehicle, and is provided with a pair of arm portions pivotally mounted to the frame of the vehicle and a body portion connecting the pair of arm portions.

The hollow parts of the arm portions and the body portion of the instant swing arm are filled with ^a the foam resin.

Because of the foam resin in the hollow parts of the arm

portions and the body portion composing the swing arm, when a vibration is transmitted from the engine to the swing arm, the foam resin absorbs the vibration so that the arm portions and the body portion are not vibrated, thus preventing the resonance.

The foam resin may fill up the hollow portions of the arm portions and the body portion as exemplified or ^{only that} ~~just the~~ part of the swing arm where the resonance is most easily generated.

The foam resin used to fill the hollow portions can be, for example, urethane foam, polypropylene foam, polystyrene foam, polyethylene foam, acrylonitrile-styrene resin foam, gum-based foam, or urethane foam having gum-based particles.

Alternatively
[Or, at least two ~~or more~~ of the following may be used in combination:

urethane foam, polypropylene foam, polystyrene foam, polyethylene foam, acrylonitrile-styrene resin foam, gum-based foam, and urethane foam having gum-based particles.

These foam resins have excellent resistance to heat generated from the engine and to oil products such as gasoline and are also excellent in terms of cost and endurance. Further, having respectively different qualities, these foam resins may be optionally used in accordance with the structure of the two-wheeled motor vehicle, the volume of the engine or other requirements.

If the urethane foam to be used has a density from 0.010

to 0.100, it is possible to effectively control the resonance due to the engine vibrations. Further, urethane foam having gum-based (solid) particles can exhibit an excellent function. In this case, the density of the foam product is preferably from 0.050 to 0.500.

A method of producing the swing arm of this invention is as follows.

The swing arm for a two-wheeled motor vehicle has hollow portions in the arm portions and in the body portion, and a part or all of the hollow portions are filled with a foam resin. The production method of this swing arm includes a process for introducing a quantity of the raw material of the foam resin into the hollow portions and a process for foaming the introduced raw material.

The raw material of the foam resin is introduced through threaded openings formed in the swing arm for attachment to the vehicle or through openings provided at the end sides of the swing arm. Therefore, there is no need to provide specific openings dedicated to for introducing the raw material.

Another production method manufacturing for the two-wheeled motor vehicle swing arm in this invention is as follows.

This method fills at least a part of the hollow portions is filled with a previously molded and foamed material. Chips of previously molded foam material, a gum-based foam, or a synthetic

gum material are inserted into the hollow portion of the swing arm, thereby reducing the production steps and increasing the production efficiency. Also, in this case, as the chips of the foam material are inserted into the opening for attaching members to the vehicle as mentioned above, it is not necessary to specifically and separately provide an opening.

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 ^{is a cross-sectional end view} shows explanatory views of the swing arm filled with the foam resin;
- Fig. 1B ^{is cross-sectional side view of the swing arm filled with the foam resin} shows an enlarged view of an essential part of Fig. 1;
- Fig. 3 ^{is another} shows an enlarged view of an essential part of Fig. 1;
- Fig. 4 ^{is} shows an explanatory view of a jig to be used for filling with expandable beads;
- Fig. 5 ^{is} shows an explanatory view of ^{another} a jig to be used for filling with expandable beads;
- Fig. 6 ^{is a perspective} shows an explanatory view of ^{the swing arm for explaining} a procedure for filling with expandable beads;
- Fig. 7 ^{is} shows an explanatory view of a procedure for filling with expandable beads;
- Fig. 8 ^{is} shows an explanatory view of ^{another} a procedure for filling with expandable beads;
- Fig. 9 ^{is} shows an explanatory view of ^{yet another} a procedure for filling

with expandable beads;

Fig. 10^{is} shows an explanatory view of the procedure for filling with expandable beads;

Fig. 11^{is a perspective} shows an explanatory view of the procedure for filling with expandable beads; *(swing arm for explaining the)*

Fig. 12^{is a perspective} shows an explanatory view of another jig for filling with expandable beads;

Fig. 13^{is a perspective} shows an explanatory view of another method for filling with expandable beads; *the swing arm for explaining*

Fig. 14^{is} shows an explanatory view of another method for filling with expandable beads;

Fig. 15^{is} shows an explanatory view of another method for filling with expandable beads; *step in a*

Fig. 16^{is} shows an explanatory view of another method for filling with expandable beads; *yet*

Fig. 17^{is} shows an explanatory view of another method for filling with expandable beads; *still*

Fig. 18^{is a perspective} shows an explanatory view of the swing arm to be used in the embodiments shown in Figs. 12 through 17;

Fig. 19^{A is a cross-sectional end view of a swing arm and} shows explanatory views of another jig and a process used in for filling with resin foam such as urethane foam;

Fig. 19^{B is a cross-sectional side view of the assembly shown in Fig. 19A;} shows an enlarged view of the jig shown in Fig. 19; *perspective*

Fig. 21^{is} shows an explanatory view of another method for *yet*

filling with resin foam such as urethane foam; and

Fig. 22^{is 2 perspective} [shows an explanatory] view of a motorcycle having a general swing arm. ✓

MOST PREFERRED EMBODIMENTS FOR PRACTICING THE INVENTION

An embodiment of the invention will be described with reference to the attached drawings. The materials and layouts used in this invention are not restricted to those described in this specification; they may be modified within the scope of the invention.

A swing arm S for a two-wheeled motor vehicle according to the embodiment is used as a rear fork of a two-wheeled motor vehicle such as a motorcycle and is composed of a pair of arm portions 10 and a body portion 20 located between the two arm portions 10. The arm portions are pivotally connected at one end thereof to the frame of the motor vehicle (not shown) and may be able to tilt with respect to the frame. The opposite ends of the arm portions 10 support the rear wheel (not shown) of the motor vehicle.

The arm portions 10 are elongated and generally square-shaped in vertical cross section and are formed with a projection 11 extending downward from the vehicle body so as to ^{add} secure stiffness. Further, one of the arm portions 10 has a pivot pipe 10b welded to its end, said pivot pipe being designed to engage a shaft member (not shown) provided at the ✓
✓

vehicle frame. Further, the other one of the arm portions 10 has an end piece 10d welded to the opposite end thereof, said end piece being formed with a rear wheel 10c.

As shown in Fig. 2, the arm portions 10 have an opening 10e at one end of the end piece 10d for attaching a member to the arm portions. As shown in Figs. 2 and 3, in case the foam resin is formed by means of foaming beads, the opening 10e is used to introduce the beads-foaming material and steam. Further, the opening 10e may be also used to introduce ~~the~~ chips of previously formed foam material into the hollow portion.

The body portion 20 is formed with a bracket (not shown) projecting upward to be connected to a spring (not shown) of a suspension device. The body portion 20 is a hollow member connected to the arm portions 10 at the sides of the vehicle body.

The arm portions 10 and body portion 20 are formed as one body in a casting process or may be separately formed and connected by welding.

The arm portions 10 and body portion 20 have openings 10a and 20a provided at the upper side thereof as shown in Fig. 1A and 1B. The openings 10a and 20a are used as the threaded openings for mounting the swing arm S to the vehicle body, and in this embodiment, the openings 10a and 20a are ^{also} used as the openings for introducing the foam resin and steam into the hollow portion.

of the swing arm S, which will be mentioned later.

According to the present embodiment, the arm portions 10 and body portion 20 of the swing arm S are filled with the foam resin which has a good heat resistance. ^a [Namely,] since the swing arm S is disposed in the vicinity of the engine of the two-wheeled motor vehicle, it is preferred that the foam resin will not be denatured due to the heat generated from the engine. Further, ^a the foam resin having a good oil resistance is used so that it is not denatured by contact with gasoline or the like. It is ^{a/s} more preferable that the foam resin ^{be} is inexpensive and does not readily deteriorate.

To obtain foam resins satisfying the above-mentioned conditions, several ^{Types} ~~sorts~~ of raw materials have been examined and compared. [The] comparisons have been made with respect to heat resistance, oil resistance, cost, and endurance. As a result, it has been found that ² the preferred foam resins are urethane foam, polypropylene foam, polystyrene foam, polyethylene foam, ⁵ acrylonitrile-styrene resin foam, gum-based foam (cross-linked foam), and urethane foam having gum-based particles. Further, since these foam resins have inherently different qualities, suitable foam resins are selected in accordance with the structure and ^{size} ~~volume~~ of the two-wheeled motor vehicle. For example, when the cost is important, a polystyrene foam is selected. When ^{resistance} ~~the~~ heat is

important, urethane foam, gum-based foam (cross-linked foam), urethane foam having gum-based particles, polyethylene foam, or polypropylene foam is selected. Further, these foam resins may be used in optional combinations.

b Further ^a or, one or ^a an optional combination of urethane foam, polypropylene foam, polystyrene foam, polyethylene foam, and acrylonitrile-styrene resin foam may be mixed with ^{the} urethane foam having gum-based particles.

Especially, urethane foam is preferable with respect to heat resistance, oil resistance, and cost. Further, urethane foam is easily adhered to aluminum and has excellent mechanical properties for absorbing vibrations. Further, since the foaming [rate] may be [comparatively] delayed, urethane foam may easily be formed in the interior hollow portions of the arm portions 10 and body portion 20. To obtain such a preferable ^{red} condition with urethane foam, the foam density should be from 0.010 to 0.100.

Further, gum-based foam or urethane foam having gum-based particles may be used to effectively prevent resonance with vibrations of the engine.

In the case of urethane foam mixed with gum-based urethane or urethane having gum-based particles, it is preferable to foam the raw urethane liquid to a density of 0.050 to 0.500.

[Now,] the jigs and the method for filling the swing arm S

for the two-wheeled motor vehicle with foaming resin beads will *now* be explained with reference to Figs. 4 through 18. In *[The] describing* *embodiments shown in* Figs. 4 through 11, the explanation will be for an embodiment in which the foaming beads are introduced into the swing arm S and then heated by steam to form the foam resin. The foaming beads mentioned herein are pellets or particles having a foaming agent previously combined therewith. The foaming beads have excellent dispersion of foaming agent and form a uniformed cell structure. ✓

The used *[]* *include*
For the *jig* for filling *[up]* with the foam resin, *[]* a material introducing jig 31 and steam injecting jig 32 *are used* as shown in Figs. 4 and 5. *[Said]* jig 31 is connected to a hose extending from a material tank and introduces the foaming beads to the swing arm S, and *[said]* jig 32 injects the steam for heating the foaming beads. ✓

As shown in Fig. 4, the material introducing jig 31 has an *[connecting]* opening 31a to be connected to the hose extending from the material tank and a raw material exhaust opening 31b, which is engaged with the opening 10a provided at the arm portions 10 of the swing arm S.

As shown in Fig. 5, the steam injecting jig 32 has an opening 32a to be connected to a hose extending from a steam generator and a pair of steam pipes 32b to be inserted into the member attaching openings 10e of the swing arm S. The steam pipes

32b are provided with apertures for injecting the steam.

Next, the method for filling the interior hollow portions of the swing arm S with the foam resin by use of the jigs 31, 32 will be explained.

5 In the first step, as shown in Fig. 6, the openings 10a, 20a of the swing arm S are closed by a mesh sheet, except the opening to be used for injecting the foaming beads. This is to prevent the foaming beads from leaking from the openings 10a and 20a. The closing of the openings by the mesh sheet allows the air to flow out, since the material filling machine is driven by compressed air so that the material flows by air pressure. ✓

The second step is to introduce the foaming beads. As shown in Fig. 7, the raw material exhaust opening 31b of the raw material introducing jig 31 is engaged with the opening 10a of the swing arm S which is not closed by the mesh sheet. Then, the material filling machine is operated to introduce the foaming beads.

The third step is to inject the steam to heat and foam the foaming beads which have been introduced into the hollow portion of the swing arm S. [The air is] As shown in Fig. 8, ^{air is} injected while the steam pipes 32b of the steam injecting jig 32 are inserted into the member attaching openings 10e. As shown in Fig. 9, when foaming is finished, the steam pipes 32b are pulled out from the swing arm S.

Where the foaming is not sufficient because of the distance of the foamable material from the steam pipes 32b of the steam injecting jig 32, the steam pipes 32b are inserted into the closer openings 10a or 20a to heat the foaming beads as shown in Fig. 10.

The fourth step is, as shown in Fig. 11, to turn down the side of the swing arm S into which the steam pipes 32b are inserted to drain and dry the same. Thus, the swing arm S wherein the arm portions 10 and the body portion 20 are filled with the foam resin is manufactured.

Figs. 12 through 17 show explanatory views of another embodiment of the jigs and the method for filling [up] the swing arm S with the foam resin. According to the embodiment shown in Figs. 12 through 17, opening 10a or 20a ^(see Fig. 6) formed in the swing arm S is attached ^{to structural} [with] a member. It is, therefore, impossible to introduce the raw material and inject the steam at the opening 10a or 20a. In this case, the material is introduced and the steam is injected through the member mounting opening 10e shown in Fig. 13. ✓

In this embodiment, the foaming beads are manually introduced into the swing arm S, and only the steam injecting jig 33 shown in Fig. 12 is used. The steam injecting jig 33 has a connecting opening 33a which is connected to a hose extending from the steam generator and a steam pipe 33b which is inserted into the member mounting opening 10e of the swing

arm S. The steam pipe 33b has apertures for injecting the steam.

According to the present embodiment, since a member is attached to the opening 10a or 20a of the swing arm S, it is impossible to reheat a non-foamed ^{portion by} place with inserting the steam pipe into ^{2 not the} a desired opening. Therefore the steam pipe 33b of the steam generator 33 is elongated so as to supply the steam to a terminal of the swing arm S.

Further reference will be made to a method for filling the hollow portion of the swing arm S with foam resin by use of the steam generator 33.

In the first step, in case ^{where} the swing arm S has openings other than the opening for introducing the raw material, the openings are closed with a mesh sheet to prevent the foaming beads from leaking therefrom.

The second step is to introduce the foaming beads. The member mounting openings 10e are directed upward as shown in Fig. 14. Then the foaming beads are manually introduced into the swing arm S at the openings 10e.

The third step is to inject the steam and then heat and foam the foaming beads which have been injected into the swing arm S. The steam is, as shown in Fig. 15, injected at the openings 10e through the steam pipe 33b of the steam generator 33 which is inserted into the openings 10e. When the foaming is finished, the steam pipe 33b is pulled out from the swing arm S as shown

in Fig. 16.

The fourth step is, as shown in Fig. 17, to turn down the side of the swing arm S where the steam pipe 33b was inserted to drain and dry the swing arm S. Thus, the swing arm S, wherein the arm portions 10 and the body portion 20 are filled with the foam resin is manufactured.

According to the above ^{described} mentioned embodiment as shown in Fig. 1A and 1B the swing arm S has the arm portions 10 and the body portion 20, ^{most} part of which are designed to be filled with the foam resin. ^{Alternatively,} the foam resin may fill up only a part of the swing arm S, for example, in the body portion 20 and in the vicinity thereof where resonance is easily generated.

In case the foam resin fills up only a part of the hollow portion of the swing arm S, a wall may be previously formed, when the swing arm S is molded, ^{to divide that} between a part of the hollow ^{from that portion} [portion] that the foam resin fills up and a part of the hollow portion ^{not to be filled with} that the foam resin does not fill up, thereby to ^{shown in Fig. 17} ~~appropriately fill up the desired part with foam resin.~~

According to the embodiment ^{shown in Fig. 17}, in addition to the material introducing jig (not shown), a steam injecting jig 34 and a steam ^{venting} absorbing jig 35 are used ^{as shown in Fig. 17}. The steam injecting jig 34 has an opening 34a to be connected to a hose extending from the steam generator and a steam pipe 34b to be inserted into the openings 10a or openings 20a of the swing

arm S. The steam pipes 34b are provided with apertures^{for} steam injecting.

The steam^{venting} ~~absorbing~~ jig 35 is used to ^{remove} ~~absorb~~ surplus steam injected into the swing arm S, and has the opening 35a to be connected to an external hose and ~~absorbing~~ pipes 35b to be inserted into the openings 10a or openings 20a of the swing arm S. The ~~steam absorbing~~ pipes 35b are provided with apertures at which the steam ^{enter} ~~is absorbed~~.

To fill with the foam resin with the method described in this embodiment, the swing arm S has, as shown in Fig. 18, openings 10a and openings 20a into which the pipes of the steam injecting jig 34 and the steam^{venting} ~~absorbing~~ jig 35 are inserted.

The method of this embodiment for filling with the foam resin is characterized by a steam heating process. Namely, as shown in Fig. 17, when heating the foaming beads which have been introduced into the swing arm S, the steam pipes 34b of the steam injecting jig 34 and the ~~steam absorbing~~ pipes 35b of the steam^{venting} ~~absorbing~~ jig 35 are inserted into the openings 10a or openings 20a of the swing arm S, and the injection and the ^{venting} ~~absorption~~ of steam are simultaneously carried out.

Thus, according to the heating method of this embodiment, the steam may be ^{uniformly} ~~equally~~ supplied within the swing arm S. The water produced by cooling the steam is ^{drained off} ~~absorbed~~. The surplus water is prevented from adhering to the interior of the swing

arm S.

As shown in Fig. 18, in case the swing arm S can be formed with openings at a certain spacing, a chamber system is preferable ^{to} ~~instead of~~ the steam injecting and ~~absorbing~~ ^{venting} system ^{using} ~~by use of~~ the steam injecting jig 34 and steam ~~absorbing~~ ^{venting} jig 35 as shown in Fig. 17. With employment of this chamber system, the work to insert the steam pipe and the ~~absorbing~~ ^{venting} pipe may be eliminated, and the operation efficiency may be increased. Further, the quality may be improved if the steam openings are evenly provided.

Figs. 19 and 20 show ~~explanatory views of~~ another method for filling up the swing arm S with the foam resin. According to this embodiment, the swing arm S is filled with foam resin such as urethane foam instead of using the foaming resin beads ^{described} ~~as mentioned~~ above. In this embodiment, the foam resin to be used may be urethane foam, gum-based foam, ~~and~~ urethane foam having gum-based particles or the like.

The raw material for the foam resin is introduced by use of the jig 36 as shown in Fig. 20. The jig 36 has an opening 36a for receiving the foam material and an opening 36b for ^{introducing} ~~exhausting~~ the foam material ^{into} ~~to~~ the swing arm S. The jig 36 may be arranged at a recess provided adjacent to the member mounting opening 10e and may introduce the foam material through the member mounting opening 10e.

[Further,] Fig. 21 shows another embodiment in which the foam material may be directly injected by means of a float or a tube.

[Namely,] Instead of the jig 36, a tube 37 is attached to the end of an injector and the other end of the tube 37 is inserted into the hollow portion through the member mounting opening 10e to inject the foam resin.

According to the present embodiment, the foam material used is, for example, urethane foam, gum-based foam, or urethane foam having gum-based particles. Of course, an optional combination of these foam resins may be used.

[As to ^{for} the] cooling and drying of the swing arm S after it has been filled with the foam resin, the swing arm S may be allowed to spontaneously cool and dry as in the other embodiments. Vacuum cooling will make it possible to cool and dry efficiently and in a short time.

Further, according to the ^{present} embodiment, the foam material is foamed in the hollow portion of the swing arm S. It is, however, possible to fill up the hollow portion with a previously molded foam material. In this case, the foam material is previously molded and made into chips, and then the chips are used to fill up the hollow portion. The chips may be obtained from unneeded molded foam products or may be the waste chips produced when molding the foam material. Thus, a waste material may be recycled.

INDUSTRIAL FIELD OF APPLICATION

According to this invention, since the hollow portion of the arm portions or the body portion constituting the swing arm is filled with the foam resin, the foam resin will absorb the vibrations transmitted to the swing arm from an engine, thereby reducing the vibrations of the arm portions and body portion and preventing resonance.

The foam resin used to fill the hollow portions can be, for example, urethane foam, polypropylene foam, polystyrene foam, polyethylene foam, ^{or} acrylonitrile-sty^rlene resin foam. These ~~foam resins have excellent resistance to the heat generated~~ from the engine and to oil products such as gasoline and are also excellent in terms of cost and endurance. Further, these foam resins, which inherently have different qualities, may be optionally used in accordance with the structure of the two-wheeled motor vehicle, the volume of the engine or other requirements.

ABSTRACT

A swing arm [5] for a two-wheeled motor vehicle ^{is} composed of a pair of arm portions [10] connected ^{by a} [10] body portion [20], the arm portions [10] and the body portion 20 having hollow portions, at least a part of ^{which are} the hollow portions of the arm portions 10 and the body portion 20 is filled with a foam resin.